



DONCELLA

GOTON TILES INC
5455 E La Palma Ave, Unit C, Anaheim, CA 92807
Tel: 714-695-0366 · Fax: 714-695-0367
E-mail: orderdesk@gotontiles.com · <http://www.gotontiles.com>

DONCELLA

MARBLE COLLECTION



DONCELLA

IVORY



Wall | Doncella Ivory SAT Rect. 24\"/>

PACKING LIST

	SIZE DENOMINATION	WORKING SIZE	THICKNESS	BOXES					PALLET					
				PCS	M²	KG	PCS/M²	KG/M²	PCS	BOXES	M²	KG	HEIGHT (CM)	SIZE (CM)
SATIN	24\"X48\" RECT.	23.42\"X47.24\"	10 mm	2	1.43	30.38	1.40	21.27	80	40	57.12	1,240	75	95X120
	48\"X48\" RECT.	47.24\"X47.24\"	10.5 mm	1	1.44	34.00	0.69	23.61	36	36	51.84	1,300	75	120X140
POLISHED	24\"X48\" RECT.	23.22\"X46.85\"	10 mm	2	1.40	33.21	1.42	23.39	72	36	50.55	1,215	75	100X120
	48\"X48\" RECT.	46.85\"X46.85\"	10.5 mm	1	1.42	34.50	0.71	24.36	36	36	50.98	1,300	75	120X140

UNE-14411-STANDARD CLASSIFICATION: PORCELAIN (BIa) / PORCELAIN CLAY (BIb)

CHARACTERISTICS	STANDARD	BIa	BIb	EVALUATION
WATER ABSORPTION	UNE-EN-ISO 10545-3	Ev ≤ 0,5%	0,5%<Ev ≤ 3%	Complies
BREAKING STRENGTH	UNE-EN-ISO 10545-4	≥ 1300 N	≥ 1100 N	Complies
MODULUS OF RUPTURE	UNE-EN-ISO 10545-4	≥ 35 N/MM2	≥ 30 N/MM2	Complies
SURFACE ABRASION	UNE-EN-ISO 10545-7	Declared value	Declared value	Class 4
CRAZING RESISTANCE	UNE-EN-ISO 10545-11	Requested	Requested	Complies
FROST RESISTANCE	UNE-EN-ISO 10545-12	Requested	Requested	Complies